June 1976 NSRP 0002

SHIP PRODUCTION COMMITTEE
FACILITIES AND ENVIRONMENTAL EFFECTS
SURFACE PREPARATION AND COATINGS
DESIGN/PRODUCTION INTEGRATION
HUMAN RESOURCE INNOVATION
MARINE INDUSTRY STANDARDS
WELDING
INDUSTRIAL ENGINEERING
EDUCATION AND TRAINING

THE NATIONAL SHIPBUILDING RESEARCH PROGRAM

Proceedings of the REAPS Technical Symposium

Paper No. 5: SPARDIS -- A Shipyard Production and Control System

U.S. DEPARTMENT OF THE NAVY
CARDEROCK DIVISION,
NAVAL SURFACE WARFARE CENTER

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments arters Services, Directorate for Information	regarding this burden estimate mation Operations and Reports	or any other aspect of the property of the pro	nis collection of information, Highway, Suite 1204, Arlington
1. REPORT DATE JUN 1976	TE 2. REPORT TYPE N/A			3. DATES COVERED	
4. TITLE AND SUBTITLE			5a. CONTRACT NUMBER		
The National Shipbuilding Research Program: Proceedings of the REAPS Technical Symposium Paper No. 5: SPARDIS A Shipyard Production and Control System			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NU	JMBER
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center CD Code 2230 - Design Integration Tools Building 192, Room 128 9500 MacArthur Blvd Bethesda, MD 20817-5700				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/M	ONITOR'S ACRONYM(S)	
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NO	OTES				
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF				18. NUMBER	19a. NAME OF
a. REPORT b. ABSTRACT c. THIS PAGE unclassified unclassified unclassified			ABSTRACT SAR	OF PAGES 41	RESPONSIBLE PERSON

Report Documentation Page

Form Approved OMB No. 0704-0188

DISCLAIMER

These reports were prepared as an account of government-sponsored work. Neither the United States, nor the United States Navy, nor any person acting on behalf of the United States Navy (A) makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness or usefulness of the information contained in this report/manual, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or (B) assumes any liabilities with respect to the use of or for damages resulting from the use of any information, apparatus, method, or process disclosed in the report. As used in the above, "Persons acting on behalf of the United States Navy" includes any employee, contractor, or subcontractor to the contractor of the United States Navy to the extent that such employee, contractor, or subcontractor to the contractor prepares, handles, or distributes, or provides access to any information pursuant to his employment or contract or subcontract to the contractor with the United States Navy. ANY POSSIBLE IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR PURPOSE ARE SPECIFICALLY DISCLAIMED.






Proceedings of the REAPS Technical Symposium June 15-16, 1976 Atlanta, Georgia

Research and Engineering for Automation and Productivity in Shipbuilding

10 WEST 35 STREET CHICAGO, ILLINOIS 60616



© 1976 IIT RESEARCH INSTITUTE

ALL RIGHTS RESERVED - NO PART OF THIS BOOK MAY BE REPRODUCED IN ANY FORM WITHOUT PERMISSION IN WRITING FROM HT RESEARCH INSTITUTE EXCEPT TO OUGHE BRIEF PASSAGES IN CONNECTION WITH A REVIEW FOR A TRADE PUBLICATION OR THE PRESS.

SPARDIS--A SHIPYARD PRODUCTION AND CONTROL SYSTEM

John J. McQuaide
Charles S. Jonson

National Steel and Shipbuilding Company
San Diego, California

Mr. McQuaide is Vice President of Yard Operations at NASSCO. He has over 40 years of experience in the shipbuilding industry from supervising hull construction to production and engineering.

Mr. Jonson is a Chief Production Planner at NASSCO where he performs as assistant manager in the Production Control Department.

INTRODUCTION

SPARDIS provides NASSCO with a tool to use one of its most valuable resources - information. SPARDIS is desiged to provide various levels of management with the information they need to better perform their function. It is intended that the task of providing this information be accomplished with the least amount of paper work. To do this, all of the SPARDIS information is in the form of on-line, real time, data inquiry and update. Data is collected, updated and maintained for the system through a network of communications terminals. These terminals are located where data is originated, the system user area. The communications terminals are located throughout the shipyard at Strategic locations for both inquiry and update. Responsibility for data input is placed in the area organizationally responsible for its creation and maintenance. The teleprocessing system permits decisions to be made based on the latest information available. As a management tool for planning and scheduling SPARDIS provides:

- .Explicit Schedule and instructions to make parts, assemble components install. equipment, etc.
- .Management reports including:
 - -Status of items in the manufacturing cycle
 - -Work behind schedule
 - -Progress to date against the schedule
 - Status of inventory items needed
 - -Definition of future work
- Projection of material requirements.
- Consolidation of work load by operation.
- Control of the in-process inventories.
- A consistent part-task identification method.
- Engineering progress record.

I SPARDIS


SPARDIS is an acronym for Scheduling Planning And Reporting Data Information System. It is a tool designed to assist in the scheduling and planning associated with the construction of ships. The system is designed to permit visibility of this planning at various levels. It permits a high level overview as to the status of large sections of the ship as well as visibility down to the smallest part.

SPARDIS is designed to use a numbering system as the key to the information base. This numbering system is used throughout the shipyard so that a number assigned to a part is the same number used by Engineering, Material, and Production. The number associated with a part becomes its name and this name is allways used to identify the part. There are two basic classes of numbers used in SPARDIS. One is the Material Code Number which is the number used to identify raw stock. The other is the Manufactured Piece Number.


Except for the contract code assigned, the Material Code Number is completely numeric. It takes the form of either six or eight numeric digits. The first two characters indicate the material class (e.g. 01 is Pipe, 82 Steel, etc.) The next four characters indicate the specific commodity and size. If present, the last two digits represent the level of essentiality and shock grade.

MATERIAL CODE NUMBER

FOR PURCHASED PARTS



The other numbering format is for the manufactured Piece Number. This is distinguished from the Material code Number by the presence of an alphabetical letter in the first position following the contract code. The rest of the characters are always numeric. The first position, which is alphabetic, denotes in which Ship Section or general area of the ship the item is used. The second position, which is numeric, denotes the level of importance to the parent assembly or task. The remaining characters of the piece number are filled first with a hyphen for consistent spacing, and a series of from one to five numeric characters. These numeric characters to the right of the hyphen, bear no significance to the part number, except. that they tend to be sequentially assigned. Thus they are termed "non-signi-In order to separate part and assembly numbers ficant but sequential". pertaining to one group of ships from numbers designated for another group, an alpha-character has been imposed preceding the first position of the SPARDIS further analyzes a piece number by distinguishing parts from assemblies and tasks by use of the piece numbering system. A part (being an item which is fabricated exclusively from a single source item) is designated by either a number "8" or "9" found in the "level" position of the part number. An assembly (being the joining in some manner of two or more parts) is designated by the number 7 thru 1 depending on the level of structure it is on the ship. SPARDIS says "the smaller the number in the `level' position of an item number, the greater significance this item has in the total structure." For example, an A6 assembly, is of greater significance than an A8 part, and an A3 assembly, is of greater significance than the A6 assembly and so on. The ship section codes and the "level" indicators are described further on the following pages.



Ship Section Identification:

All part, assembly, system, compartment, task and event numbers are prefixed with an alphabetical charecter to indicate the appropriate group within Engineering or Production planning responsible for their assignment. The ship section numbers are as follows:

ALPHA	RESPONSIBLE	
CHARACTER	GROUP	DESCRIPTION
A B C D	HUIL ENGINEERING HULL ENGINEERING HULL ENGINEERING HULL ENGINEERING	HULL STRUCTURE FOUNDATIONS HULL FITTINGS CARPENTRY
E F	(OPEN)	(OPEN)
G H	HULL ENGINEERING HULL ENGINEERING	RIGGING SCIENTIFIC (WAYS)
J	(OPEN)	(OPEN)
К	ELEC. ENGINEERING	POWER & LIGHTING
L	(OPEN)	(OPEN)
M N	ELEC. ENGINEERING ELEC. ENGINEERING	ELECTRICAL STANDARDS ETECTRICAL
Q	PROD. PLANNING	NASSCO STANDARD PARTS (AIL SHIPS ALL CONTRACTS)
P R S T V	MACHINERY ENGINEERING MACHINERY ENGINEERING MACHINERY ENGINEERING MACHINERY ENGINEERING MACHINERY ENGINEERING MACHINERY ENGINEERING PROD. PLANNING	PIPING VMACHINERY MACHINERY MACHINERY VENTILATION SPEC. ITEMS
x	PROD. PLANNING	COMPARTMENTATION,
Υ	PROD. PLANNING	MAJOR TASK/EVENT COMPARTMENTATION
Z	(OPEN)	(OPEN)

Manufacturing "Level" Numbers:

The "level" indicator denotes the level of importance to the parent assembly or task, not necessarily its position in the network. The manufacturing 'level" indicators are as follows:

LEVEL	ASSIGNEE	DESCREPTION
1	PRODUCTION PLANNING	A SPECIFIC TASK OR EVENT, AREA OF THE SHIP, OR SYSTEM NUMBER
2	PRODUCTION	a unique erection assembly consisting of two or more parts and/or two or more $6,5,4,$ or 3 LEVEL assemblies that erect directly into the HULL
3	PRODUCTION PLANNING	A UNIQUE ASSEMBLY CONSISTING OF TWO OR MORE PARTS AND/OR TWO OR MORE $6,5,4,$ OR 3 LEVEL ASSEMBLIES THAT NEXT ASSEMBLE INTO ANOTHER $(3\ \text{or}\ 2\ \text{LEVEL})$ ASSEMBLY.
4	PRODUCTION PLANNING	A UNIQUE ASSEMBLY CONSISTING OF TWO OR MORE PARTS AND/OR TWO OR MORE $6,5,$ OR 4 LEVEL ASSEMBLIES THAT NEXT ASSEMBLE INTO ANOTHER $(4,3,OR$ 2 LEVEL) ASSEMBLY.
5	PRODUCTION PLANNING	A UNIQUE ASSEMBLY CONSISTING OF TWO OR MORE PARTS AND/OR TWO OR MORE ${\bf 6}$ OR ${\bf 5}$ LEVEL ASSEMBLIES THAT NEXT ASSEMBLE INTO ANOTHER $({\bf 5,4,3,}$ OR 2 LEVEL) ASSEMBLY.
6	PRODUCTION PLANNING	A UNIQUE ASSEMBLY CONSISTING OF TWO OR PARTS THAT NEXT ASSEMBLE INTO ANOTHER (6, $5,4,3,$ OR 2 LEVEL) ASSEMBLY.
7	ENGINEERING - PRODUCTION	A STANDARD MINUFACTURED ASSEMBLY HAVING SUFFICIENT REQUIREMENTS TO JUSTIFY STAND-ARDIZATION AND BATCH-MANUFACTURE. COMPLETE INTERCHANGEABILITY IS MANDATORY.
8	ENGINEERING	A STANDARD MANUFACTURED PART HAVING STANDARDIZATION AND BATCH-MANUFACTURE. COMPLETE INTERCHANGEABILITY IS MANDATORY.
9	ENGINEERING	A UNIQUE MANUFACTURED PART HAVING A LIMITED REQUIREMNT TO THE EXTENT THAT A STANDARD CANNOT BE JUSTIFIED.

STANDARD PARTS & ASSEMBLIES

An 8 "level" part in the SPARDIS System is defined as:

"A standard manufactured part having standardization and batch-manufacture. Complete interchangeability is mandatory."

Similarly a 7 "level" assembly is defined as:

"A standard manufactured assembly having sufficient requirements to justify standardization and batch-manufacture. Complete interchangeability is mandatory."

The intent of the 7 & 8 "levels" in the SPARDIS numbering system is to account for those parts and assemblies that are used in sufficient quantity that it is economical to batch manufacture them. Confusion often arises due to the many interpretations possible for the term "batch manufacture". Let us examine some of the criteria which must be considered-for something that is to be "batch manufactured" in an attempt to clarify some of this confusion.

One of the first things to consider is that an item, in order to be considered a standard, must be relatively small. This is true because we want to handle the material in groups of parts rather than one-at-a-time. Therefore one of the things we must consider is the ability to handle the material economically.

Complete interchangeability is also required because we want to be able to manufacture a group of these parts for inventory and withdraw them as necessary for use. Another thing to consider then is the set-up time to manufacture certain items. Let us take, as an-example, a ladder which requires a jig to be set-up. It is more economical to make several ladders at one time with one set-up than to set up the jig everytime a ladder is required. Assemblies such as ladders are not the only items to consider for set-up time. Any part that requires a template could be considered in this category. Every time a part is manufactured that requires a template, someone has to locate the template, bring it to the material, lay it out, and then produce the part. If this is done several times with a single template the cost will be correspondingly high. Therefore set-up time does become part of our criteria.

Let us discuss a part of the criteria which has produced much confusion and attempt to clarify it. How do we determine, based on the number of parts required, what we should classify as a standard? If a part or assembly is used only once on a hull, it is, by definition, unique and therefore cannot be considered for a standard. We might be tempted to say that if a part is used more than once it should be a standard. This might make the decision process quite simple, but it would not be adequate for production needs. We must first determine if the two or more parts are used in more than one assembly. For example, let us assume that we require ten flat bar stiffners for a foundation. Let us further assume that these flat bar stiffners are all identical and are only used in this one foundation. In this case since there is only one demand for the parts, the foundation, we would consider these stiffners unique. This is true because they will be totally consumed on one assembly. If, however, the same ten stiffners were used in more than one assembly, let's assume five in one foundation and five in another, we would consider these stiffners stadard parts. We have, then, derived another part of our criteria. In order for a part to be considered a standard it must be used in more than one assembly on a hull.

Using the criteria we have developed we can now formulate several questions which can be used to test a given part to see if we should call it a standard.

- 1. Is the part/assembly small enough to be handled and stored easily?
- 2. Is there more than one part/assembly required?
- 3. Are the parts/assemblies used in more than one assembly?
- 4. Does that set-up time warrant producing more than one at a time?

If the answers to these questions-were all "yes", then we have determined that this part/assembly should be classified a standard.

If we are to be able to produce several parts/assemblies at any given time we will require some knowledge of when we are going to manufacture them and ensure that the raw material is available. We must ensure there is sufficient material on hand to produce our standards in economical groups or lots. In order to do this both Engineering and Planning must be involved. Engineering must determine the total requirements for the standard and their approximate locations so that Planning can determine when to manufacture the standards and in what quantities. This information, once developed, can be used to determine what raw materials are required and when they should be purchased. It is important that total requirements are determined so that we do not over-manufacture a part.

If all of these criteria are used properly "batch manufacturing" can produce significant cost savings to the shipyard.

11 MASTER FILES

The information database that defines the plan for the task of putting together the thousands of parts in a ship, is designed to functionally define the elements of that plan. These functional elements the structure, description, routing and schedule. In fact, SPARDIS has as its base, four master files which allow the proper definition of these elements. Let us examnine each of these elements and their associated files and content to better understand how the information is maintained.


The Description File contains the definitions of what the part assembly is. It allows the user to give meaning to the name given to a part 1 For example:

The description File can also be used to define a task. For example:

P2-250 Complete installation of innerbottom piping fr. 78-85 cL.

In other words the Description File contains the definition of parts, assemblies, or tasks. Each part, assembly or task in the plan is defined in the Description File.

The Structure File defines what pieces are required to go together to produce the next level of assembly. That is, it is a "goesinto" type of definition. The Structure File defines what parts, assemblies or tasks go together to form new assembly or task. This type of an arrangement of parts is also known as a hierarchical arrangement or a bill-of-material. In building the Structure File, the top level-task (parent) will have secondary level tasks or "component-parts" attached to it. The structure created till he a single, top level task (assembly) with a horizontal string of component parts (referred to as the second level). To add parts vetically to the structure, the second level is considered the parent task and attached to it are its component parts (now becoming the third level of the original task or assembly). This procedure is repeated until the structure is complete. The following illustration will clarify the complete concept. Take the following structure:



This structure can be broken down into separate single-level structures as follows:

This is the method used to enter the structure into SPARDIS. The Structure File defines what "goes into" the next level as well as what raw material is required to manufacture the associated parts.

The Structure File is the networking capability within the SPARDIS System. As will be seen, the network can be time phased to produce data for material requirements planning (MRZ) and other useful management tools. One area of confusion often arises when discussing the SPARDIS piece numbering system and the Structure File. That is, the "level" number in the piece number as opposed to the level in the hierarchy. The "level" indicator has no relation to a components position in the structure file. It is merely an indication of the complexity of the component.

The Routing File defines where operations are to take place to manufacture each level of the structure. We define the operations by assigning work stations which are the places operations will be performed to produce the defined levels of the structure. In order to produce these parts and assemblies, time must be allocated to each operation so that a previous operation is completed prior to beginning the next and so on. In other words, component items must be routed through each designated operation in such a manner as to be completed in time to become part of the next assembly level. In order to accurately accomplish this the phasing, SPARDIS uses Lead Days, or a number of planned work days to complete a given task at a particular operation. These operations are performed at designated work stations and each work station is assigned the number of lead days necessary to accomplish the task. Consequently, if we add up the number of Lead Days for each operation, we will see the total number of lead days necessary to complete the individual task.

As items in SPARDIS are routed, each work station must be made aware of what specifically is required at that operation. To accomplish this, there is a group of numeric instruction codes set up with their verbal meaning contained in the Description File. As an item is routed, the work stations are assigned an instruction number. Based on what is required at that work station, a number is picked from the Description File that applies to that requirement. This "Instruction Code" is placed in the Routing File with the applicable work station and lead days, to provide detail instructions for the planned production of a given item.

The Schedule File defines when the major tasks or assemblies must be complete in order to produce the ship in an orderly fashion. A single calendar date for each major network or structured task is placed in the Schedule File. These dates, one for each major task, taken collectively form the sequence in which the ship is to be built. This date, refered to as the base date or Work Authorized and Released date, is used to determine other key dates for each major task. These key dates are also carried in the Schedule File for monitoring progress against each major task individually. Each major task scheduled in the Schedule File then contains its own set of key dates. These dates are for the following functions:

PRODUCTION

Material Requisition
Material Receipt
Lofting Ccmplete
Work Authorized & Released
Sub-Assembly (Shop) Camplete
Erection (Installation) Complete

Fitting

Welding

Inspection

Also tracked within SPARDIS are key dates for both Engineering and Specification Material ordering. These are:

ENGINEERING

Drawing Start thru Approval

Actual Submittal Dates

Actual Performance Dates

Actual Approval Dates

Schedule Dates - Navy (Vendor Information thru issue)

Actual Dates - Navy (Vendor Informtion thru % Complete)

MATERIAL ORDERING

Inquiry Information

Vendor Plans

Purchasing Information

Schedule Delivery

Promised Delivery

Actual Delivery

SUMMARY

These four files, (Description, Schedule, Structure, and Routing) form the Data Base of defined tasks that must be accomplished in order to build ships to specification, schedule and cost limits. the planning base from which work is released and monfrored throughout the shipyard. All the subsequent information in SPARDIS is created from the Description, Structure, Routing and Schedule Files.

III WA/R FILE

To provide the information that is necessary to actually produce the components, the Work Authorized and Released (WA/R) File is created. Periodically, a parameter date (some date into the future) is selected. Using this date all major tasks or assemblies that fall within this parameter are selected from the Schedule File. These major task numbers are then used as keys to the Structure File. In turn each component of the associated structure is collected. These new keys in turn are used to select the associated routing and lead days from the Routing File. Since we started with a date from the Schedule File when the task or assembly must be complete, and we found what the components of the assembly are, and the operations and the number of days to perform each operation, we can compute schedule start and complete dates for each operation of each component of the structure. This process is called a parts explosion or more commonly a "Chase". This procedure produces the WA/R File.

The WA/R File is the base from which an analysis of Material Requirements is made. It is the file from which shop order documentation is produced to fabricate or assemble components. Actual progress of the various components is reported in this file. Therefore, at any time during the production phase of a part or assembly, inquiry can be made to determine the actual status and location of a given item.

SUPPLEMENTARY FILES

In addition to the five files which have been described (Description, Structure, Routing, Schedule, and Work Authorized/Released) there are an additional set of Supplementary files which are created and maintained from these for ease of use of the teleprocessing system. These are:

Inventory Status and Multiple Location

Detail Requirements by Date

WA/R Cross Index

Parts Cross Index (Structure)

Source Item Cross Index (WA/R)

MWR Cross Index (Shop Order)

Inventory Status/Multiple Location File

An Inventory Status Record is created for all common and nested parts. This record contains the primary location of the item and the quantity on hand at that location. It also lists the total (to date) quantities required, ordered, received, issued, staged (obligated), and a cumulative on hand total (total on hand quantity). In addition, there are other quantity fields that are used in specific processing, such as the Economic Lot Order size, a preliminary estimate of the total quantity required for a contract; and an Adjustment quantity to maintain a record of quantities known to be lost or erroneously used.

The Multiple Location Record is used to contain the secondary locations for items stored in more than one location. This record has the capability of holding five (5) locations (in addition to the primary location in the Inventory Status Record) and carries an on hand quantity for each location. This provides for a total of six location fields within the SPARDIS inventory system.

THE TOWN OWN CONTROL OF THE PARTY OF THE PAR

Detail Requirements by Date File

After the WA/R data is generated, those requirements flagged as "standard" or "common" (nested), in other words "Inventory items", are extracted. A Detail Requirement Record is established which reflects the date and quantity of the item required. The use of additional processing steps relating to the Detail Requirements File, determines those items that have not been manufactured to support a specified date. This is accomplished by allocating the ordered and released quantity in the Inventory Status to the requirements that exist in the Detail Requirements File in date sequence. When the ordered quantity allocated to requirements is insufficient, additional parts are released to the WA/R File in economic lot order size, as found recorded in the Inventory Status Record.

This process results in establishing the quantities of Inventory Items to be made with a positive date for completion. The same process that creates the WA/R file at the time of Chase is utilized to extract the manufacturing instruction necessary to make the Standard and Common Parts.

WA/R Cross Index File

The WA/R Cross Index File is created by extracting data from the Work Authorized/Released File and sorting it in next assembly sequence. The associated displays indicate the status of work complete and locations of the next assembly structure for a given assembly's number as it is currently shown in the WA/R File.

Parts Cross Index File

The Parts Cross Index File and its associated on-line, real time display, indicates all places that requirements exist for a given material code, part number, or assembly piece number. Data is removed from the Structure File and is sorted in source item reference number sequence. Any updates to the Structure File, are automatically reflected in the Parts Cross Index File.


Source Item Cross Index File

The Source Item Cross Index File is compiled from data extracted from the WA/R file and is sorted in required date sequence. The associated display shows "where it is used" information pertaining to both raw material source items (for parts) and line item sources (for assemblies). Information displayed is real time and reflects only those records currently contained in the WA/R file.

MWR Cross Index File

The Material Withdrawal Request *Cross* Index File is used for requesting the issue of purchased material from the warehouse. Its major key is its MWR number which is the same as the Shop Order number used in our Shop Order number to *list* all purchase items necessary to-produce a given task. These items are then ordered through the MWR System using the Shop Order number as the key.

Figure 1 is an illustration of the use of these supplementary files for ease of access to the data base. These files are developed to permit efficient use of the teleprocessing system for the user.



SPARDIS Application

Using the basic concepts discussed, let us examine how we can apply these concepts to control the massive task of building a ship. To do this we must provide management with the visibility to the initial planning effort and later to the actual production progress.

We must provide:

- 1) Definitions of the boundaries of tasks and events precisely.
- 2) A list of major tasks that combine many "erection units" into a single event or task.
- 3) As early as possible, material requirement information to ensure accurate material requirements planning (MRP) data.
- 4) A data base from which we can extract the data necessary for actual progress vs. the plan.

Utilizing the Description File we establish a list of key events or tasks which define the major measuring posts that must be passed in order to complete the ship. The SPARDIS keys or numbers for these tasks begin with "X1-". The numbers and their definitions are developed by Production Planning in conjunction with the production supervision. Examples of some of the types of events used are:

- Xl-1 Land main turbine.
- X1-2 Complete installation of boat davits and their associated winches and equipment.
- X1-7 Complete installation of pump room package prior to erection of 30' flat.

These events are then scheduled in relation to the major milestones such as keel, launch and delivery. The schedules for the major tasks are input into the Schedule File. The Schedule File then contains a set of event related completion dates which taken collectively, form the sequence in which the ship is to be built.

The defined tasks or events now form one level of our hierarchical arrangement. Continuing, we develop the supporting tasks in order to further define the component structure of the major task. Production Planning begins by defining these assemblies or packages of work in the Description File. These lower level components are generally prefixed by an "'X'1-" or "'X'2". For example let us call one of these lower level components A2-65 which we will define as the structural unit "Innerbottom unit 6" port to 29' off CL stbd., C-D-E3 stks, girders, transverse floors, frame 71 to 6" aft of frame 85 starboard". This unit which is part of the pump room is then structured as a component of the event which it will support. All other components of the event are also defined and structured. These components form another level in our hierarchy.

Each of these components becomes the parent assembly and their component structures are added until the raw material components are reached. In this manner we have created a multi-level hierarchical arrangement of components beginning with the highest level monitoring post.

Let us examine one of these major tasks to better understand the data base we are creating. We will use as our example:

X1-7 Complete installation of pump room package prior to erection of the 30' tlat.

Figure 2 is an illustration of where the pump room is located in the ship. It consists of the supporting structure as well as the major pump room components. The structure of this package can be simplified by looking only at the major components. This structure will take the following form: STRUCTURE OF X1-7:

LINE	COMPONENT	DESCRIPTION
01	A2-35	BOTTOM SHELL PLATING
02	A2-64	INNERBOTTOM - PORT
03	A1-65	INNERBOTTOM - STBD W/PIPING
04	A2-129	TRANSVERSE BHD FR 71 PORT
05	A2-130	TRANSVERSE BED FR 71 STBD
06	P2-30	PIPING THROUGH TANK TOP
07	P2-22	PUMP ROOM PIPING TANK TOP TO 30' FLAT
08	A2-157	LONG'L BHD PORT
09	A2-152	SIDE SHELL
10	A2-159	TRANSVERSE BHD FR 80 STBD
11	A2-160	LONG'L BHD STBD
12	A2-158	TRANSVERSE BHD FR 80 PORT
13	W2-21	BUTTERWORTH HEATER & DRATIN COOLER


Each of these components in turn have their own structural components. For example A1-65 has as its components: STRUCTURE OF A1-65:

LINE	<u>COMPONENT</u>	<u>DESCRIPTION</u>
01	A2-65	INNERBOTTOM - STBD
02	P2-20	INNERBOTTOM PIPING


These in turn have their own component structures. This process is continued in a "top down" planning sequence until the *lowest* level component is reached. In this manner we have formed a detail network of the events leading up to the completion of the task. You will note that the component number has no relation to its position or level in the structure.


Figures 3 through 7 are given for illustration of the concept.


Each of these components is described, structured, and routed in the SPARDIS System. Routinely the four master files (Description, Schedule,




-XI-7 PUMP ROOM PACKAGE FIGURE 2









Structure, Routing) are combined through a parts explosion or chase process. This allows a scheduled start and completion date to be applied to the network.

This new set of data, called the Work Authorized/Released File, is used to examine material availability. To do this the WA/R data set is compared to the inventory and purchase order files and exception reports are generated. These exception reports are used by the purchasing department for expediting material to ensure material availability. WeeKly, a portion of this WA/R data set is used to prepare detail prduction information to construct the ship. This information is in a special form called shop orders. A shop order is prepared for each level of the structure and is used both as an authorization for work and as a progressing tool in the shipyard. Data is maintained in the WA/R File as-to the actual status of components, with their location, in real time. This data is routinely entered into the system via remote terminals which are strategically placed throughout the shipyard. Status and progress information is available to anyone in the shipyard by a simple inquiry on one of these terminals.

SHOP ORDER SYSTEM

The Shop Order provides 2 means of authorizing production to produce a component in the shipyard. The shop order is a computer generated document which provides the necessary information to accomplish a single task. It is a tool which allows shipyard management to allocate the resources necessary to accomplish specific tasks. The shop order documents are tied directly to the withdrawal of purchased components as will. be shown later.

The shop order system has three primary components (See Figure 8) :


- 1) shop Order a printed document providing the necessary information to accomplish a single task. The shop order card is a three-part snap-out form, $8\ 1/2\ x\ 5\ 1/2$ inches in size. The first sheet of the set is a yellow light-weight original, the second sheet is a green light-weight carbon copy and the third sheet is a heavy card stock carbon copy.
- 2) Work Station Schedule Log a printed document which provides a list of shop orders for a specific work station, in date order. The work station schedule log is printed on standard computer paper $8\ 1/2\ x\ 14$ inches.
- 3) Teleprocessing System a system of communication lines and terminals used to communicate with the Spardis system. These terminals are used for both inquiry and updating of the work in process. This permits the user to make decisions in his dynamic environment based on the latest information available. His-decision making is aided in the knowledge of the latest status information as well as knowing where to go to get a part or assembly.

Weekly, as part of the chase or parts explosion process, shop orders are printed for work which has been authorized by Production Planning. A separate shop order is printed for each operation for each level of the network. That is, each work station that is to perform work on a specific component receives its own shop order. The shop orders are bundled, by work station, by scheduled start date, with the appropriate Work Station Schedule Log. As shop orders are printed, a number is attached to the shop order and its corresponding WA/R File record. This number is used in ordering purchased material from the warehouses as well as for filing purposes. The number is non-significant.

The work station schedule log is designed for use by the production foreman. It lists all work to be started on a specific day and indicates when each shop order must be completed to support the next level of events in the network. Space is provided for any annotations desired by the foreman.

The shop order provides detailed instructions to clearly define the planned task. However, space is provided on the shop order form for the foreman to indicate any additional operations that must be performed.

The Shop Order System Consists of:








Three part snap-out form with carbons

WORK STATION SCHEDULE LOG

Foreman 's listing of jobs per

Work Station per day.




TELEPROCESSING SYSTEM (CRT)
Informational inquiry and
Work Station Update.

AND YOU -----THE USER

When the operations indicated have been performed the three copies of the shop order are used as follows:

- 1) Yellow turned in to the Production Control Department to indicate the task is complete. In turn the corresponding WA/R File record is updated showing when the work was accomplished.
- 2) Green shipping document, a traveler attached to the component to get it to its next work station; or discarded if the task level has been reached.
- 3) Heavy Card Stock returned to the foreman so that he may update his records. If additional operations were required the form is returned to Production Planning so that the corresponding records can be corrected for any subsequent releases. It becomes a feed back document.

The shop orders are used throughout the shipyard and are the instrument by which material is progressed through its fabrication, assembly and installation cycles. Figure 9 is a diagram of the use of the shop orders. Figures 10 & 11 are examples of shop orders and work station schedule logs, respectively.



Section & Page No.: Revision No.:	
Revision Date:	

PURPOSE: SCOPE :		FREQUENCY :	REPORT N	umber: <u>S6127</u>
To provide a printed hard-copy document that authorizes and releases to Production the information necessary to accomplish a specific task at a specific work Station. Details instructions for the sin tile fabrication of Parts & the performance of tasks. The authorizea Production to accomplish the performance of tasks.	Asoembllen & e SHOP ORDER	Daily, from 360-3 Transmittal Form & following a Final Chane.	Title: SHOP ORDER	
		اــــــــــــــــــــــــــــــــــــ		·
	<u> </u>	<u> </u>	<u> </u>	<u> </u>
HUP ORD 382611-2 ***/5 025 TH ATEN ROLLS (AT SOUTH END OF RAISED SLAB) SOLET START DATE 04/27/6 (AT 398-100-009 HALL 398 PRI/UP 001 SUB/UP 035. EF R A9-2073 REL 001 LNE 000 CXCO 2089 QTY EMPLOY (SEE 1NST) (A 7) TIMB! ((2 DVG 398	D 302609-6 ***/\$ 035 J; -100-009-64 - 02-8 t-106, REL DU: LWE do: 2-106 REL	HALL TOS PRIVOD DOS SUDJO CKCD 1020 GTY SC- BIDE SHELL G-H-J-K-L-M SHARKSI 18 TAFF BI TO 18 TAFF BI THE CHARGE	STARY DATE 05/07/4
NST3L/O TU W-2PC (MIS-14). 6 RML SETS B FR-81-1/4.82,52-1/2.82-3/ .63-1/4.84-12 CKS (RIS-1-5)	INSTEASS	SENOLE AS PER DETAILS C	H DRAYING. TIME CHARG	E NO 6398-100-009-
I CD HEF NO HEL GIV UI MS - DESCRIPTION/REMARKS 2 826043 I EA AM PL 26-775#X127\ASO		1-239 FA 1 6106 S	DELL PLATING ACCY.	DRYAINE.
(ADDITIONAL OPENATIONS)		-203 EA 1 VERTIC	BI TO BA. PORT. AL WEB FRAME, ON SIDE SHELL. BE PORT. STIFFS AFT. AL WEB FRAME. ON SIDE SHELL.	398-100-009-06B-02-U
		1-204 MA 3 VERTIC FRAME 1-205 MA 1 VERTIC	AL VES FRAME. ON SIDE SHELL. BB. PORY. STYFFS AFT. AL WES FRAME. ON SIDE SHELL.	
		FRANE	84. PORT. STIPPS AFT.	249-110-014-11V-03-44
	306 2-49	(515 #00)		395-100-009
		(SIS #88 1		398-100-009
	007 2-49		4"X1/2"X35*-03"	398-100-009
	DO8 2-A0	H-2135 KA .J.AN 8™X	4"X1/2"X35*~03"	354-100-009
P	009 2-49	-2137 EA (SIE 808)	4"X1/2"X35"-03"	398-100-009
b	010 6-49	7 884 812) -2139 EA 1 A3 10-	X4"X-44/-75X35"-03=	[]
	© _		• •	398-100-009
 	0	•	CONTINUED	' [2]
Sample of SPARDIS computer-generated SHOP ORDER card for a unique, individual Part number. Actual size of card: 8-1/2" x 5-1/2".			r-generated SHOP ORDER ca e of card: 8-1/2" x 5-1/2	
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXX	<u> </u>	<u> </u>
(1) SHOP ORD - Computer-assigned SHOP ORDER identification number.	3 REF		es the Bull Code & the SP	
W/S = 3-digit Work Station & description of Work Station. START DATE = The scheduled work date that the fabrication of	REL		Piece Number) identificat s the Release Number of the	
Reference Number should commence.	LNE	- Specifie	s the Line Item within the	e Reference Number's
The gradific bluesmint (Dunning) & leasting that	CKC	structur	al matrix for the specific	Rclease indicated.
2 <u>Dws - The specific blueprint (Drawing) & location that Reference Number can be viewed.</u>	CKC	negāte i	-assigned Check Code. Ihis mproper updates (such as a	number tranasposition
HULL - The NASSCO-asaigned Hull number.	^	by perso	nnel entering on-line upda	ating.
Indicates the previous operation or Work Station that the Reference Number was shipped from.	<u>Q</u>	T Y Indicate for this	es the quantity of the Refe particular Release Number	c. erence number reduited
sub/or - This field indicates all subsequent Work Station(a)			•	
that the Reference Number must progress through before completion of this Level:	(C	ontinued on next page)	
Wollde Completed of Mile 20101	(0)	onimuca on neat page	")	

28

N A S S C O - SPARDIS USERS' HANDBOOK

Section & Page	
Revision Revision	

PURPOSE:	SCOPE :		FREQUENCY:	REPORT	Number: S6127
To provide l printed hard-copy document that authorizes l and releases to Production the Information necessary to l accomplish l specific task at a specific Work Station.	Details instructions for the in the fabrication of Parts & the performance of tasks. The lauthorize production to accompany	& Assemblles & ne SHOP ORDER	Daily, from 360-3 Transmital Form & following . Final Chase.	Title: SHOP ORDI	<u></u>
		1,	1 , 1 , 1		
HOP ORD 382612-2 **** BZS PLATEN ROLLS EAT SOUT WE 398-180-009- HRLL POB PRIMP EF R A9-2073 REL OOI LHE 600 CKCD 2849 QTY /A R A3-259 DEL. PL 26-7758X116-XA RA2-106 REHARKS: **** NSTEL/O TO W-2PC [VIS-141. 6 RILL SETS B YR.81-1. 63-1/4.84-12 CKE (RIE-1-5)] I CO REF MO REL OIT UK MS** DESCRIPTION/REMARKS I EA AH PL 26-7758X122X489	001 SUB/OP. 038: TRAPT OATE 04/27/4 001 SUB/OP. 038: TEMPLOC (SEE INST) () 1/2=X36=-00= 1/2=X36=-00= 0 /4.02.02-1/2.02-34	2 DUG 398- 3	-100-009-6A - 02-8106 REL 001 LNE 001106 REL 001 REL 001106 REL 001 REL 001106 REL 001 REL 001106 REL 001 REL 001107 REL	CKCD Jean STY CSC. SIDE SHELL.G-HI-J-K-L CHARKSI ISPAFY AI TO ISPAFY SHE BRANDING. CITIES CHARKSI ISPAFY AI TO ISPAFY CHARKSI ISPAFY CHARKSI ON SIDE SHEE CAL WEST FRANCE. ON SAFE CAL WEST SAFE	TEMPLOC (ASSEMBLE) A STRAKES, WITH CONTINCE A STRAKES, WITH CONTINCE A PORT. BROWN BANK BANK BANK BANK BANK BANK BANK BAN
Sample of SPARDIS computer-generated SHOP individual Part number. Actual size of ca	ORDER card for a unique, rd: 8-1/2" x 5-1/2".	Sampl Work	e of SPARDIS compute Station. Actual siz	er-generated SHOP ORDER te of card: 8-1/2" x 5-1	card for an Assembly
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	CXXXXXXXXXXXXXXXXXX	X X X X X X X X X X X X X X X X X X X		(XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
(Continued from last page) TEMPLOC = Template Location: S ASSEMBLE indicates t Station 035 is to we modular component Re HEIGHT - TONS = Indicates the accumulation weight factor does no	pecifies the storage location of hat all of the component Parts ld all of the components & part ference Number R A2-106. lated weight (short tons) of all of include the weight of wald of lso assists Riggers in assignment	of HOLD LOFT-prepar have already been (tabulated in Do 1 of the individual or other joining man	red Layout & fabrica layed-out & fabrica stail (5) above) togo al Parts for Level I edium. On a Part Lev	tion templates. On the state, thus the function of the to produce the state Assemblies and for Level, only the weight of	above sample, the word of this Assembly Work ructurally complete els 3 through 7. This the Part itself is
M/A Indicates the Next A Final Assembly reflet R A3-239 as its Next Indicates the Final DESC This field describes the	ssembly to which the Reference cts self-finslization because th Assembly; subsequently R A3-239 Assembly for the Reference Numb the Reference Numder.	Number is deatined is Unit is a Leve) moves to R A2- 1 er. Reference Number.	l. On the above right l 1 Erection Sequanc 06 and will become a	t-hand sample for R A2- re. The left-hand sample n intcgral part of R A2	106, both the Next & for R A9-2073 indicate -106.

(SIS #89)

CONTINUED

Purposes:	SCOPE:	FREQUENCY:	REPORT Number: S6127	
To provide a printed hard-copy document that authorizes and releases to Production the information necessary to accomplish • specific task at a specific Work Station.	Details instructions for the steps required in the fabrication of Parts & Assemblies & the performance of tasks. The SHOP ORDER authorizes Production to accomplish .sccomplleh work,	Daily, from 360-3 Transmittal Form & following a Final Chase.	Title: SHOP ORDER	
	$\overline{}$		-	
EF R AP-2073 REL DOI LNE 000 CKCD 2089 GTY /A R A3-23P DESC. PL 26-775#X118- /A R A2-106 REMARKSI NSTIL/D TD V-2PC (V18-14). 6 MAL SETS 3 TR-01-1. 1 CD REF NO REL DIY U1 -> DESCRIPTION/REMARKS 2 820043 I EA AN PL 26-775#X122X450	1/2=x366-00= 1/2-x366-00=	0-100-009-6A - QZ-8 12-106 REL ODI LNE DOC 12-106 REL ODI LNE DOC 12-106 RESENDLE AS PER DÉTAILS (REF NO. UI OVY 13-239 EA 1 SIDE 3 FRANE 14-203 EA 1 VERTIC 15-106 PER NO. UI OVY 14-205 EA 1 VERTIC 15-106 PER NO. UI OVY	DESCRIPTION DESCRIPTION SHELL PLATING ASSY S 81 TD 84 PORTS S 98 TO 90 PORTS S 98 TO 90 PORTS S 98 TO 90 PORTS ASS	
Sample of SPARDIS computer-generated SHOP ORDER card for a unique, individual Part number. Actual size of card: 8-1/2" x 5-1/2". Sample of SPARDIS computer. generated SHOP ORDER card for an Assembly Work Statlon Actual size of card: 8-1/2" x 5-1/2".				
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX				
LNE CD REF NO UI OTY DESC DESC				

- Alerts the user that the next Line Item of structure is continued on the next SHOP ORDER card.

Refers to a separate document "Supplemental Instruction Sheet" that more fully defines special or complex fabrication data.

END

Section & Page No.:	
Revision No.:	
Revision Date:	

PURPOSE: To provide a computer-generated printed document for Production Foremen which tabulates complete daily scheduled tasks for each Work Station under his supervision - for projecting maximum utilization of facilities. SCOPE: Two-fold: (1) Provides a composite tabulation of the daily scheduled tasks for individual Work Stations, listing Start & Complete dates (2) By issuing the Log to Foremen several work-days in advance, maximum utilization of available manpower, equipment & machine-loading can be realized.	Title: HORK STATION SCHEDULE LOG
OLIA 4 DAT PREPARED 05-00-76. WILR KS TATION SCHE OV MURKS TO THE FEMARKS TO COMPLETED CHIP FEMARKS TO COMPLETED BY	DULE LOGGOSS TO WORK START DATE 06-10-6 UI DTY REV SOURCE 1 TEP N/A F/A PRI COMPLETE OP DATE
05257-7 389 A9-6106 QOZ	EA 021402 1 A2-406 A2-406 001 06-14-0

05259-3 .1119 A9-6107 002 .	EA 821402 1 A2-407 A2-407 001 06-14-0
05281-7 389 A9-6095 00g	EA 821458 1 A3-620 A2-485 001 06-14-6
05294-0 389 A9-6096 002	EA 621458 1 A3-621 A2-486 001 06-14-6
END PLANT	
	1-1-1-
DATE PREPARED - The date that the computer produced this print-out, 2	7 N/A - Indicates the Next Assembly of Reference No. 8 F/A - Indicates the Final Assembly of the Next Assy. 9 PRI OP - Indicates the previous Work Station of Ref. No. 10 COMPLETE DATE - Specifies the scheduled completion date of Reference Number.
END	1

Material Withdrawal Request MWR)

The material withdrawal request system is a method by which purchased material is withdrawn from warehouses by production. It also provides a means by which the material requirements established in the SPARDIS system may be analyzed against total shipyard inventory and outstanding purchase orders.

The data in the MWR system is developed by extracting purchased material requirements from the WA/R File. These requirements, which are time phased, are first compared to the inventory on hand. This comparison begins by allocating the material on-hand to the requirements until the total on-hand quantity is consumed. At this point the Purchase Order File is examined and any outstanding purchase orders for the commodity are compared to the required quantities and their corresponding required dates. In this manner a set of data is generated from which a series of reports is created. Among these reports is an analysis of outstanding requirements by vendor, by commodity and by the production "Work package" (SPARDIS assembly). These reports form the basis of the material requirements planning (MRP) tools incorporated into the SPARDIS System.

The second phase of the MWR system deals with the actual withdrawl of material. As has been stated previously, this portion of the system is tied directly to the Shop Order. In developing shop orders for printing following a chase or parts explosion, a cross index to the WA/R file is developed. This cross index is developed for use of the teleprocessing system as a means of access to the WA/R data via the shop order number. The data being accessed, by way of the shop order number, is the same.data as appears on the shop order. As part of the production process the production foreman examines his shop orders to determine which assemblies require purchased material. When he determines he is ready to proceed with the construction of an assembly, he simply requests the issue of material through the teleprocessing system. This request is then analyzed in relation to the material on-hand as described previously. The material is then obligated to the requested end-use and a withdrawal ticket printed by the computer. The withdrawal tickets are printed in such a manner that a group of commodities for a single assembly are printed by warehouse location. That is, if materials for a given assembly are located in more than one warehouse, then a separate ticket for each warehouse is printed. Separate documents are also prepared to allow for the staging or kitting of components from several warehouses. This permits the delivery of purchased components as a complete package of material to the appropriate work station, rather than the work station receiving a group of material from several warehouses and having to sort through the material to get the components they require for a specific job. This system is designed to permit a minimum amount of work-in-process and maximize the use of the data available for MRP. Since issues-from the warehouse can be recorded in real-time, via the teleprocessing system, the inventory records tend to be more accurate than with "batch" systems.

Examples of several reports are presented in figures 12 thru 14. Figure 12 is a sample of one of the material analysis reports depicting commodities for which the material on-hand will be exceeded. Figure 13 is a sample of a material analysis report showing the assemblies scheduled that will be impacted by material shortages. Figure 14 is an example of an MWR ticket.

PURPOSE: To provide a "tool" to review the planned processes for filling material requirements & to assist in material purchases, expediting and production release decisions.		report, listing which the invent e requirements fo	tory on-hand	FREQUENCY: Daily, and following the Preliminary & Final Chases.	Title: MATER	REPORT Number:	
				•			
			-d	<u></u>			
	ν			<u> </u>		2	
(¹) (²)		🧐 🕠	φ	9			
H1628 DATLY - HA	TERIAL SI	HORITAGE	Ψ	R T - 1/5	04/13/76		PAGE 15
HATE CODE DESCRIPTION SIZE	} _{DATĒ} (4) .=:	ACY HAND	C PO NO 1	ORDER	O HUL REF NO	OUTREMENTS X	- REL OTY
59-00-0853 STAT.OP.REMOTE.STOW#9879	RIHMS						
1º (8 TPI).STOW -517-16 \	V 11TY-P "04-23-5			2	10965 393 R3-01	001_85-93_	
PR TO	1117-P 04-23-5	9 9- 11- 11-	- H - H		10989 393 R3-103 05037 393 R3-63	001 R2-64	001 7
PRIOF	1117-P 04-29-5 _	25- 27 25- 27-	 		05070 393 R3-67 05095 393 R3-101	001_R2-66 001_R2-73	001 14
, r n au-	02-05-6 02-05-6	27- 20- 27- 10-	- M RO3198 (
	02-05-6	2716-	_M_R03284_(001 2			(
	02-05-6 02-05-6	27- 0	M R03525 (002 14			
	02-05-6	27~ 1	N R03791 (
59-00-0854 STAT DE RENDTE STOWN 879- 1 (16 TPI) STOW -534-16		o o			******	001 R2-53	001 2
	ATED-X 04-24-5 ATED-X 03-04-6	6			10924 393 R3-69 08764_393 R3-67	800 R3-87	
	ATED-X 03-04-6 RITY-P 03-04-6	0 0		ģ	08765 393 R3-50 08766 393 R3-41	800 R3-50 800 R3-41	800 2
	02-05-6 02-05-6	2- 0 2- 1	H R02871 (H R03832 (
1	1	1	·	1.	1	1.	
	<i>'y</i>			<u>//</u>	—		
NASSCO-assigned matused primarily for written certificati	piping, valves - bu	it are also appli	cable to cert	ain other highly s			
2 DESC/SIZE - Detailed description	n of Material Code.						
(3) (Prioritized issue) ~ Indicates the	current "priority	of issue precede	nce" for thes	e items most criticoduction and thus	ically needed by Proshould be given pr	oduction. At the	discretion edence
over other 1t	ems can be so flagg	ed directly on-l	ine (via CRT	Display SEL/YEL)	thus modifying the	issue sequencing	order.
The term OBLI	that the material i	s a material with a required for i	narawai keque nstallation i	nto an Assembly -	printed, but mater or - the Promised	Date for the Pure	chase Order.
(5) ON HAND: ACT - The actual on-hand							
required amount. PROJ - Anticipated on-hand							
(6) CT - NASSCO-assigned Cor	tract identification	on code.					
			Inued on next	page)			

8ection & Page	No.:
Revision	No.:
Revision I	Date:

PURPOSE: To provide a "tool" to review the planned processes for filling material requirements & to assist in material purchases, expediting and production release decision. SCOPE: Exception report, Iisting those commodities for which the inventory in lees then the requirements from Chase process	on-hand Daily, an	g the ary &	REPORT Number: H 1 6 2 8 Title: MATERIAL SHORTAGE REPORT		
	——————————————————————————————————————	ν.		<u> </u>	$=$ ν $=$
MISSO DAILY - MATERIAL SHORTAGES	(1) REPORT - 1/3	·	04/13/76	05:27	PAGE 1
	PO NO ITH SN	OTY S	O HUL REF NO	DUTREMENTS	- REL OTY
59-00-0853 STAT. 09-REHOTE. STOY #9879 RIHHS					
PRIORITY-P 04-23-5 2- 9- H PRIORITY-P 04-23-5 11- 11- H		Z 109	65 393 R3-61 89 393 R3-103 37 393 R3-63	001 R2-63 001 R2-74 001 R2-64	001 2 001 7 001 2
PRIDRITY-P 04-29-52525		,_ ,2050	70 303 R3-67 95 393 R3-101	001 R2-66-	001 14
02-05-6 27- 16- N	R03198 001 R03207 001	7			
02-05-6 27- 14- M	R03284-001	<u>\$</u>			
	R03525 002 R03791 007	14 1			
59-00-0854 STAT. 0P. RENOTE. STOY#9879-RENS					
1" (16 TP1) STOW -534-16 0 8 0 8 0 8 0 8 0 8 0 8 0 8 0 8 0 8 0			24 393 R3-59	001 R2-53 800 R3-87	001 2 800 2
DBLIGATED-X 03-04-64 4 .M. DBLIGATED-X 03-04-6 0 0 M PRIDRITY-P 03-04-6 2- 2- H		9087	164 393 R3-87 165 393 R3-50 166 393 R3-41	600 R3-50 600 R3-41	800 2 800 2
02-05-6 2- 0 M I	R02871 004 R03832 001	2	700 373 K3-41		
1	/				hannan
			<u> </u>		·
(a) and another than the state of the state					
ON ORDER: Details all pending NASSCO Purchase Orders for Material Code: NASSCO Purchase Order number.	•				
The Item (or Line) number on the Purchase Order that the Mat					1400
Multiple-shipment designator (01, 02, 03, etc.). Used when dates.	a vendor promises to	o ship spe	cified qtys of the	Material Code	on different
QTY - The quantity of Meterial Code ordered on the Purchase Order.					
(B) (Date & Time) - The actual dote end time that this particular computer print-	out was made.				
(Continued	on next page)				

Section & Page Ho.:	
Revision No.:	
Revision Data:	

PURPOSE: To provide a the planned processe material requirement material purchases, production release d	s for filling a & to assist expediting an	in is	modities fo	n report, 1 or which the he requirem	inventory	on-hand	Daily, follow Prelim	EQUENCY and ing the inary & Chases.		Title:	HATER	REPORT Mu	-		
					•										
$=$ ν $=$	$\nu = -$	<u> </u>	u =	$= \nu =$	$-\nu$		<u> </u>		ν		<u> </u>	<u>/</u>		<u> </u>	
(1) (2)				③	(()	· (7) – -			••			④ .		- ·
M1626	DAILY	- HATEF	IALS	HORTA	, e ⊑ 2\	REPO		/5		04.	/13/76	05127		PAGE	1 5 U
HATE CODE DESCRIP	riān / sizë	·Ÿ- <i>-</i>	-BATÉ 4-	ACY HAN	PROJ - Ç	PO NO	N ORDER-	TYO	5 7	O HUL	REF NO	- REL F	ラマー	REL	OTY-
59-00-0053 STAT.0P	REMOTE.STON	109879 RIHM	• 1	•	^										
		-YTIAOIAG -YTIAOIAG		· · ž ·					2109	65"393	R3-01 R3-103	001 R		001	\$.
		PRIORITY-	04-29-5	11-	11- H				2050	37 393	R3-63	001 R2	2-64	001	. 2
		PRIORITY-(PRIORITY-(04-29-5	25= 27=	25H-					70_393 95_393	R3-07	- 001-R		-001	14
			02-05-6 02-05-6	27 27-		R03198		7 2	α,						
			02 - 05-6_ 02 - 05-6_	27=		.R03284. R03267		2							,
			02-05-6 02-05-6	27- 27-		R03525 R03791		14							
59-00-0854 STAT. 0P	REMOTE STO	##9879-RIHH	;								· · · · ·			*** ****	•
1- (10	TP1).STOW -	QBLIGATED-		ē	6 M				2109	24 393	R3-59	001 R		001	2
•		_DBLIGATED=1 _DBLIGATED=1	0-40-6	····· * ···-	4 M				9007	64 .393 65 393	R3-50	. 800 R	3~50	800	2
		PRIORITY-	03-04-6	2- 2-	2- H	R02871	004	2	9087	66 393	14-ER	800 R	3-41	800	2
	<u> </u>		_ 02 <u>-</u> 05-6	<u> 2—.</u>	1 _ H	R03832	001	t.						<u></u>	-
<u> </u>		1 –		1-			1 —			<u> </u>			-1 -		
PREQUIREMENTS: - S / O - HUL - REF NO - REL - F / A -	The Production Specifies the The Part Numbrus Release !	active WA/R Fi on Shop Order e Hull number per of Assembl Number of the a structured p	number on w applicable y Number wh Reference N	nich the Hat to the Shop Leh required umber.	erial Code Order, the Mater	is list	ed.		of th	a fallow	ing crit	eria:			
	(a) If (the Reference	Number is a	Sub-Level A	ssembly (L	evel 3,4	,5,6,7), t	he stru	cture	d Hext (or Final) Assembly	Number	is indica	ated.
		the Reference												not	
	part Next it's	the Reference; or multiple; (or Final) As own Part Hum	-cuts itsel ssembly Num ber in orde	f, the Refer ber will be r to automat	ence Numbe inhibited	r automa from "pe erate it	tically be gging" a n	comes a	n Inv	entory I Ion or m	tem - wi ovement :	th the res	ult that imply re	the peat	
				·											İ

PURPOSE: To identify Assemblies which SCOPE: PREQUENCY: REPORT Number: __ H1630 Exception report, listing Assemblies contain material shortages - so that which contain commodities for which the Daily, and following the they may be rescheduled, if necessary, inventory on-hand is less than the total Title: ASSEMBLIES WITH MATERIAL SHORTAGES Preliminary & by Production Planning. requirements for that commodity. Final Chases. ILY 0E61N WITH MATERIAL SHORTAGES ~ 04/13/76 05:33 PAGE 35 C HULL, _MTL.CODE_ DT_REQ 388 96-00-0150 P-SHORT 308 B2-24_ Q01 _ B2-24 82-24 001___ 001__ 339055 2 90-00-0150 01-20-6_ 030 P-SHORT_ 366 98-00-1600 12-31-5 030 P-SHORT 82-36 001 310700 050 \$2-387___001 __\$2-367 ___001 _82-387__ 355773 50-00-0680 02-23-6 _001__ 51-00-0578 02-23-6 10 030 55-00-0107 16 030 SHORTAGE 98-00-0300 02-23-6 101 030 388 82-82 P-SHORT 62-62 02~82 oöı 355604 2 98-00-3050 02-23-6 101 030 388 SHORTAGE 800 C2-222 C2-222 800 905945 50-00-0834 03-17-6 101 112 SHORTAGE" BAA 00ì Ć2~368 001 "C2-368 ooi 94-00-0080 03-31-6 94-00-0055 03-31-6 SHOR TAGE 388 C8-1069 05-04-6 ... 001 __C8-1069____001 __C8-1069___001__393734___2 __83-00-7978 002.___ 07.7_ SHOR TAGE. 368 K2-168 SHORTAGE 001 K2-168 K2-168 371794 98-00-5017 03-29-6 471 **(1)** C NASSCO-assigned Contract identification code. HULL NASSCO-assigned Hull identification number. Indicates the Final Assembly for which the material is destined. F / A Specifies the Release Number of the Final Assembly for which the material has been allocated. REL. N/A Indicates the Next Assembly for which the material is destined, REI. The Release Number of the Next Assembly for which the material has been allocated. REF The Reference Item that appears on the Shop Order number. REI. The Release Number of the Reference Item that is printed on the Shop Order. s 7 o The Shop Order number containing the Reference Item detailing. Denotes the Source Item Material Code number which specifies NASSCO's method of material acquisition. MTL CODE NASSCO-assigned Material Code identification number. $\overline{q}\overline{r}$ Specifies the quantity of Material Code required for Reference Number. Indicates the date that the Material Code must be delivered to Production. D'T REQ (Date & Time) -The actual date and time that this particular computer print-out was made. Specifies the issuing Work Station that the Material Code is to be shipped from. NXT W/S Indicates the next Work Station or Assembly area that the Reference Item is destined. (Stortage flags) - This field indicates whether or not an item has a potential shortage based on the material analysis (see REPORT M1628),

END

for high issue priority.

The word SHORTAGE indicates a potential shortage; the word P-SHORT indicates a potential shortage that has been selected

98

PURPOSE: To provide a printed hard-copy document that authorizes issue of purchased components to Production. SCOPE: Assures control of both the issue and in-house delivery point of all components to Production.	ents. FREQUENCY: REPORT Number: MHR Daily. Title: MATERIAL WITHDRAWAL REQUEST
(6)-I TA:072 LOC:PLT SHOP PRE-FAB: STEEL PLATE (7) { ISS. REQ. UI PCE MARK MAT*L CODE 1 EA 82-0593 82-00-0593 PI (8) { CONTR REFERENCE REL LNE CK.	DESCRIPTION LOC. LOC. HATL PREP B-B *LAST PAGE - END OF PACKAGE*
Specifies the Warehouse/Storage facility that will issue the Material Code (Piece Hark), Designated the in-house delivery point that the Warehouse will ship the Material Code (Piece Mark). SHOP ORDER = (D	The Work station that the Material Code (Piece Mark) is to be shipped to. Description of the receiving Work Station. Specifies the category or type of NASSCO'S Material Control Inventory system. This "blank" field is used by the issuing Work Station to manually write-in the actual quantity of Material Code (Piece Mark) issued; the manually entered qty is then updated on-line for accounting/inventory control. Indicated the qty of Material Code (Piece Mark) that is required to produce the Reference Number. Unit of Issue. The Piece Mark's measurement/qty factor Piece Mark: The Material Code Number assigned to the Piece being issued.

ction & Page No.:	
Revision No.:	
Revision Date:	

PURPOSE: To provide a printed hard-copy document	Assured control of both the		FREQUENCY: Daily.		RT Number: <u>MWR</u>
that authorizes issue of purchased components to Production.	in-houoe delivery point of a	ii components.		TITLE MATERIAL WITHO	RAWAL REQUEST
	$-\iota - \iota -$	<u> </u>	<u> </u>		
_					
1		<u> </u>		3 6	_
WHSE P	MATERIAL WITHDRAWAL RE	OUEST AREA: A	SHOP GROER 37	76524-5 CD 1	
(3) → DRWG:100-	027 REF ND:A9-10065 RE	L:001 REQ*D:04	-19-76 HULL:38	B PGE #01-01	
	LOCIPLE SHOP PRE-FAB: STEE			ETINV STA	
(15	S. REQ. UT PCE MARK MAT.	L CODE DESC	RIPTION	- 105 1 6	
0{	S. REQ. UI PCE MARK MAT.	0-0593 PL A			
		15.34	X115X246		
(a) {	REFERENCE REL LNE	CK. MATL CODE PREP			
	V A9-10065 001 000			•	
9 NCYL APPR	OVED DATE		*LAST PAGE - END	DE PACKAGE*	-(11)
	DATE 03/28/76 ISS*D	DATE		DATE -	2)
			1		
1	11		<i>L</i>		
	<u>/ </u>			<u> </u>	
(Continued) MAT'L CODE - NASSCO-assig	nod 10 ddadh manandal ddamdda.	(9	MCTL·APPROVED =		l Department must manually issuance and proper
DESCRIPTION = Detailed des	ned 10-digit material identifica cription of the Material Code.				lal Gode(s) indicated on privarding the MWR to the
	e storage location of the Materi e or storage facility.	_		issuing Warehouse or	r storage facility.
(8) CONTR NASSCO-assign	ned Contract identification symb	ol. (10	MWR PRINT DATE =		omputer printed the MWR. in the Warehouse that
	rence Number identification. control number for Reference Num	ber.		issued the material	& the date of issue.
LNE NO. = Line Item Nu	mber of the Reference Number's s	tructure.	LAST PAGE	MWR SHOP ORDER Number	
		(12	P REC'D / DATE =		s at the delivery point or this particular Warehouse
	enerated Check Code to insure the Harehouse issuance of the Piece			shipment.	
	er Contract & Reference Number i paration Code: Symbols define th				
type of raw s	material surface preparation (cl	eaning, paint,			
	ist be made <u>before</u> issuance of t receiving Work Station.	he Piece Mark			
1	•	END			

_

SUMMARY

SPARDIS is a tool for planning and controlling the shipbuilding task. It is designed to permit management the visibility to one of the company's greatest resources, information. It allows management the ability to make intelligent decisions based on the latest status of the shippard. It permits long range planning to be accomplished as well as the everyday detail release of work for the shippard. To accomplish this SPARDIS uses a common. data base concept. The common data base consists of five data files:

Description

Structure

Routing

Schedule

and created from these is the

Work Authorized/Released

The WA/R File generates reports for management and is used to release work to the shipyard. All other files in the SPARDIS System are generated from these "Master Files" for ease of access to this data base through the teleprocessing system.

As work is completed in the shipyard the data base is user updated on line, via remote terminals to provide:

Component history

Accurate audit trail

Completion status

Storage location (s)

In addition to the teleprocessing, system, management reports are generated in a routine manner. The types of reports generated are:

operational

Analysis

Exception

Additionally special reports are available on a request basis.

The concept of the SPARDIS teleprocessing system is that:

All files are on-line for data retrieval

Minimum of hard copy output

Principle method of data input

Data transmittal form optional as a back-up

Records are created in batch mode, data input and updated on-line.

Seurity feature of the teleprocessing system are established by allowing only certain terminals access to updating capability. Also certain check codes are created to ensure the proper record within a file is updated as well as the proper individual is perfoming the update. As part of the back-up system a series of transaction logs are maintained. The teleprocessing system in use at NASSCO has an average access time of between 5 and 10 seconds.

It should be re-emphasized that SPARDIS is nothing more than a tool. It is the user of the tool that allows the company to build ships in today's competitive shipbuilding environment.

Additional copies of this report can be obtained from the National Shipbuilding Research and Documentation Center:

http://www.nsnet.com/docctr/

Documentation Center
The University of Michigan
Transportation Research Institute
Marine Systems Division
2901 Baxter Road
Ann Arbor, MI 48109-2150

Phone: 734-763-2465 Fax: 734-763-4862

E-mail: Doc.Center@umich.edu